



An ICTSI Group Company

CROATIA, RIJEKA

# ADRIATIC GATE CONTAINER TERMINAL

05.01.2026

	BERTH 1	BERTH 2	
	feeder	MVS/feeder	
1. Name of terminal	ADRIATIC GATE CONTAINER TERMINAL		
2. Abbreviation / code	HRRJK		
3. Maximum depth in the channel	Depths above 40m		
4. Maximum air draft permissible above high water level	Unlimited		
5. Length of the berth	200m	428m	
6. Maximum permitted vessel length	180	400m	
7. Maximum draft at the berth	10,7m	B=42,8m -> 14,39m* + tide B=45,6m -> 14,38m* + tide B=48,4m -> 14,37m* + tide B=51,2m -> 14,36m* + tide	
*when at maximum draft vessel must: - keep list below 0,5° - keep vessel afloat at all times with minimum UKC of 0,5m			
8. Tidal range	0,60m	0,60m	
9. Operating length at maximum draft	220m	400m	
10. Vessel's side alongside	Portside	Portside	
11. Number of cranes at berth.	1 x Panamax	2 x Post Panamax	2 x Super PostPanamax
12. Outreach of Cranes / Meters & number of rows	38m	50 m	67,5 m
	13 rows	18 rows	24 rows
13. SWL of cranes under spreader	40,8mt (50mt in twin lift)	51 mt (twin lift)	51mt (65mt in twin lift)
14. SWL of cranes under hook	51mt	61 mt	75 mt
15. Number of cranes fit for twin lift ops	1	2	2
16. Minimum number of 20' bays between 2 gantries	4	4	5
17. Any restrictions on nbr of tiers that can be worked on deck	4	5	n/a
18. Maximum height of spreader from water level at low water	34m (31+3)	39 m (36+3)	55 m (52+3)
19. Over height limit (under spreader) for 20' units and 40' units	4m	4m	4m
20. Longitudinal clearance between the legs of the gantries	15m	18,3 m	18,3 m
21. Maximum cargo width	5m	5 m	5 m
22. Limitation in haz cargo that can be stowed at the terminal	Warehouse for hazardous materials in containers classes 2,3,4,5,6,8 & 9 Class 1 and 7 hazardous material to be manipulated only in direct manipulation.		
23. Reefer plugs available at the terminal	400 plugs		